

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: LOCKFAST G74

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants.

1.3. Details of the supplier of the safety data sheet

Company name: Cyanotec Ltd
Bay 2 Building 62
Third Avenue
Pensnett Trading Estate
Kingswinford
DY6 7XT

Tel: >>>

Email: tim@cyanotec.com

1.4. Emergency telephone number

Emergency tel: 0845 6183120

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: Xi: R36/37/38

Classification under CLP: Skin Sens. 1A: H317; Eye Irrit. 2: H319; -: EUH208

Most important adverse effects: Irritating to eyes, respiratory system and skin.

2.2. Label elements

Label elements under CLP:

Hazard statements: EUH208: Contains hydroquinone monomethyl ether. May produce an allergic reaction.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

Signal words: Warning

Hazard pictograms: GHS07: Exclamation mark



Precautionary statements: P264: Wash hands thoroughly after handling.

P272: Contaminated work clothing should not be allowed out of the workplace.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

SAFETY DATA SHEET

LOCKFAST G74

Page: 2

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P321: Specific treatment (see instructions on this label).

P337+313: If eye irritation persists: Get medical advice/attention.

Label elements under CHIP:

Hazard symbols: Irritant.



Risk phrases: R36/37/38: Irritating to eyes, respiratory system and skin.

Precautionary phrases: Contains hydroquinone monomethyl ether, 1-acetyl-2-phenylhydrazine. May produce an allergic reaction.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

2-CARBOXYETHYL ACRYLATE

EINECS	CAS	CHIP Classification	CLP Classification	Percent
246-359-9	24615-84-7	C: R34	Acute Tox. 4: H302; Aquatic Acute 1: H400; Eye Dam. 1: H318; STOT SE 3: H335; Aquatic Chronic 3: H412	1-10%

CUMENE HYDROPEROXIDE

201-254-7	80-15-9	O: R7; Xn: R21/22; T: R23; C: R34; Xn: R48/20/22; N: R51/53	Org. Perox. EF: H242; Acute Tox. 3: H331; Acute Tox. 4: H312; Acute Tox. 4: H302; STOT RE 2: H373; Skin Corr. 1B: H314	1-10%
-----------	---------	---	--	-------

N,N-DIMETHYL-P-TOLUIDINE - REACH registered number(s): 01-2119937766-23

202-805-4	99-97-8	T: R23/24/25; Xn: R33; -: R52/53	Acute Tox. 3: H331; Acute Tox. 3: H311; Acute Tox. 3: H301; STOT RE 2: H373; Aquatic Chronic 3: H412	<1%
-----------	---------	----------------------------------	--	-----

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

[cont...]

SAFETY DATA SHEET

LOCKFAST G74

Page: 3

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not create dust.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of dust in the air.

[cont...]

SAFETY DATA SHEET

LOCKFAST G74

Page: 4

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Polyethylene. Do not use steel containers.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency. Respiratory protective device with particle filter.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Paste

Colour: Orange

Odour: Characteristic odour

Evaporation rate: No data available.

Oxidising: No data available.

Solubility in water: Slightly soluble

Also soluble in: Most organic solvents.

Viscosity: Viscous

Kinematic viscosity: ~100000

Viscosity test method: Cone and Plate @ 25°C (CPs)

Boiling point/range°C: >35

Melting point/range°C: No data available.

Flammability limits %: lower: No data available.

upper: No data available.

Flash point°C: >93

Part.coeff. n-octanol/water: No data available.

Autoflammability°C: No data available.

Vapour pressure: No data available.

Relative density: 1.10

pH: Not applicable.

VOC g/l: No data available.

[cont...]

SAFETY DATA SHEET

LOCKFAST G74

Page: 5

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

CUMENE HYDROPEROXIDE

ORL	MUS	LDLO	5	gm/kg
ORL	RAT	LD50	382	mg/kg
SCU	RAT	LD50	382	mg/kg

N,N-DIMETHYL-P-TOLUIDINE

IPR	MUS	LD50	212	mg/kg
-----	-----	------	-----	-------

Relevant effects for mixture:

Effect	Route	Basis
Irritation	OPT INH DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

[cont...]

SAFETY DATA SHEET

LOCKFAST G74

Page: 6

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH208: Contains <name of sensitising substance>. May produce an allergic reaction.

[cont...]

SAFETY DATA SHEET

LOCKFAST G74

Page: 7

H242: Heating may cause a fire.
H301: Toxic if swallowed.
H302: Harmful if swallowed.
H311: Toxic in contact with skin.
H312: Harmful in contact with skin.
H314: Causes severe skin burns and eye damage.
H317: May cause an allergic skin reaction.
H318: Causes serious eye damage.
H319: Causes serious eye irritation.
H331: Toxic if inhaled.
H335: May cause respiratory irritation.
H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.
H400: Very toxic to aquatic life.
H412: Harmful to aquatic life with long lasting effects.
R7: May cause fire.
R21/22: Harmful in contact with skin and if swallowed.
R23/24/25: Toxic by inhalation, in contact with skin and if swallowed.
R23: Toxic by inhalation.
R33: Danger of cumulative effects.
R34: Causes burns.
R36/37/38: Irritating to eyes, respiratory system and skin.
R48/20/22: Harmful: danger of serious damage to health by prolonged exposure through inhalation and if swallowed.
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Legend to abbreviations: PNEC = predicted no effect level
DNEL = derived no effect level
LD50 = median lethal dose
LC50 = median lethal concentration
EC50 = median effective concentration
IC50 = median inhibitory concentration
dw = dry weight
bw = body weight
cc = closed cup
oc = open cup
MUS = mouse

[cont...]

SAFETY DATA SHEET

LOCKFAST G74

Page: 8

GPG = guinea pig

RBT = rabbit

HAM = hamster

HMN = human

MAM = mammal

PGN = pigeon

IVN = intravenous

SCU = subcutaneous

SKN = skin

DRM = dermal

OCC = ocular/corneal

PCP = physico-chemical properties

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.