



**SAFETY DATA SHEET**  
**CRYSTIC CRESTABOND M1-20 CARTRIDGE**

**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

**1.1. Product identifier**

Product name                                    CRYSTIC CRESTABOND M1-20 CARTRIDGE  
Product No.                                      OL1105

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Identified uses                                    Adhesive.

**1.3. Details of the supplier of the safety data sheet**

Supplier    Scott Bader  
    Wollaston  
    Wellingborough  
    Northamptonshire. NN29 7RL  
    Tel: +44(0)1933 663100  
    Emergency (24 hours) +44(0)1933 663399  
    Fax: +44(0)1933 663693  
    E-mail: reach@scottbader.com  
Contact Person                                    Regulatory Affairs Manager

**1.4. Emergency telephone number**

National Emergency Telephone Number  
+44(0)1933 663399

**SECTION 2: HAZARDS IDENTIFICATION**

**2.1. Classification of the substance or mixture**

Classification (EC 1272/2008)

Physical and Chemical Hazards	Flam. Liq. 2 - H225
Human health	Skin Corr. 1B - H314; Skin Sens. 1 - H317; STOT SE 3 - H335
Environment	Aquatic Chronic 3 - H412

Classification (1999/45/EEC)

C;R34. Xi;R37. R43. F;R11. R52/53.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Environment

The product contains a substance which is harmful to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

**2.2. Label elements**

Contains    BENZOYL PEROXIDE  
    METHACRYLIC ACID  
    METHYL METHACRYLATE

Label In Accordance With (EC) No. 1272/2008



Signal Word

Danger

Hazard Statements

H225	Highly flammable liquid and vapour.
H314	Causes severe skin burns and eye damage.

**CRYSTIC CRESTABOND M1-20 CARTRIDGE**

H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.
<b>Supplementary Precautionary Statements</b>	
P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P260	Do not breathe vapour/spray.
P261	Avoid breathing vapour/spray.
P264	Wash contaminated skin thoroughly after handling.
P321	Specific treatment (see medical advice on this label).
P370+378	In case of fire: Use foam, carbon dioxide, dry powder or water fog for extinction.
P301+330+331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P302+352	IF ON SKIN: Wash with plenty of soap and water.
P303+361+353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor/physician.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P333+313	If skin irritation or rash occurs: Get medical advice/attention.
P363	Wash contaminated clothing before reuse.
P403+233	Store in a well-ventilated place. Keep container tightly closed.
P403+235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to ...

**2.3. Other hazards****SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS****3.2. Mixtures**

BENZOYL PEROXIDE		<1.5%
CAS-No.: 94-36-0	EC No.: 202-327-6	
Classification (EC 1272/2008) Org. Perox. B - H241 Eye Irrit. 2 - H319 Skin Sens. 1 - H317	Classification (67/548/EEC) E;R2 R43 Xi;R36	
DIBUTYL MALEATE		<1%
CAS-No.: 105-76-0	EC No.: 203-328-4	
Classification (EC 1272/2008) Skin Sens. 1 - H317 Aquatic Chronic 2 - H411	Classification (67/548/EEC) N;R51/53. R43.	

## CRYSTIC CRESTABOND M1-20 CARTRIDGE

DIPROPYLENE GLYCOL DIBENZOATE		4-6%
CAS-No.: 27138-31-4	EC No.: 248-258-5	
Classification (EC 1272/2008) Aquatic Chronic 2 - H411	Classification (67/548/EEC) N;R51/53.	
METHACRYLIC ACID		6-8%
CAS-No.: 79-41-4	EC No.: 201-204-4	
Classification (EC 1272/2008) Acute Tox. 4 - H302 Acute Tox. 4 - H312 Skin Corr. 1A - H314 STOT SE 3 - H335	Classification (67/548/EEC) C;R35 Xn;R21/22	
METHYL METHACRYLATE		35-40%
CAS-No.: 80-62-6	EC No.: 201-297-1	
Classification (EC 1272/2008) Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 Skin Sens. 1 - H317 STOT SE 3 - H335	Classification (67/548/EEC) F;R11 R43 Xi;R37/38	
STYRENE		2-4%
CAS-No.: 100-42-5	EC No.: 202-851-5	
Classification (EC 1272/2008) Flam. Liq. 3 - H226 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319	Classification (67/548/EEC) Xn;R20. Xi;R36/38. R10.	
TRIZINC BIS(ORTHOPHOSPHATE)		<0.2%
CAS-No.: 7779-90-0	EC No.: 231-944-3	
Classification (EC 1272/2008) Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410	Classification (67/548/EEC) N;R50/53	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

#### Composition Comments

Urethane Acrylate Resin in reactive solvent

### SECTION 4: FIRST AID MEASURES

#### 4.1. Description of first aid measures

##### General information

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

##### Inhalation

Move the exposed person to fresh air at once. For breathing difficulties oxygen may be necessary. If breathing stops, provide artificial respiration. Keep the affected person warm and at rest. Get prompt medical attention.

## CRYSTIC CRESTABOND M1-20 CARTRIDGE

### Ingestion

DO NOT INDUCE VOMITING! NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Remove victim immediately from source of exposure. Immediately rinse mouth and provide fresh air. Get medical attention immediately! NOTE! Keep affected person away from heat, sparks and flames!

### Skin contact

Remove affected person from source of contamination. Wash the skin immediately with soap and water. Get medical attention if irritation persists after washing.

### Eye contact

Remove victim immediately from source of exposure. Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Contact physician if irritation persists.

### **4.2. Most important symptoms and effects, both acute and delayed**

### **4.3. Indication of any immediate medical attention and special treatment needed**

## SECTION 5: FIREFIGHTING MEASURES

### **5.1. Extinguishing media**

#### Extinguishing media

Fire can be extinguished using: Foam. Dry chemicals, sand, dolomite etc.

### **5.2. Special hazards arising from the substance or mixture**

#### Unusual Fire & Explosion Hazards

HIGHLY FLAMMABLE! Vapours are heavier than air and may spread near ground to sources of ignition.

### **5.3. Advice for firefighters**

#### Special Fire Fighting Procedures

Move container from fire area if it can be done without risk. Containers close to fire should be removed or cooled with water. Cool containers exposed to flames with water until well after the fire is out. Keep run-off water out of sewers and water sources. Dike for water control.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### **6.1. Personal precautions, protective equipment and emergency procedures**

### **6.2. Environmental precautions**

### **6.3. Methods and material for containment and cleaning up**

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Stop leak if possible without risk. Provide ventilation and confine spill. Do not allow runoff to sewer. Absorb in vermiculite, dry sand or earth and place into containers.

### **6.4. Reference to other sections**

## SECTION 7: HANDLING AND STORAGE

### **7.1. Precautions for safe handling**

Static electricity and formation of sparks must be prevented. Keep away from heat, sparks and open flame. Use explosion proof electric equipment. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

### **7.2. Conditions for safe storage, including any incompatibilities**

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

#### Storage Class

Flammable liquid storage.

### **7.3. Specific end use(s)**

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### **8.1. Control parameters**

## CRYSTIC CRESTABOND M1-20 CARTRIDGE

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
BENZOYL PEROXIDE	WEL		5 mg/m <sup>3</sup>			
METHACRYLIC ACID	WEL	20 ppm	72 mg/m <sup>3</sup>	40 ppm	143 mg/m <sup>3</sup>	
METHYL METHACRYLATE	WEL	50 ppm	208 mg/m <sup>3</sup>	100 ppm	416 mg/m <sup>3</sup>	
STYRENE	WEL	100 ppm	430 mg/m <sup>3</sup>	250 ppm	1080 mg/m <sup>3</sup>	

WEL = Workplace Exposure Limit.

Ingredient Comments

WEL = Workplace Exposure Limits

### METHYL METHACRYLATE (CAS: 80-62-6)

Ingredient Comments

WEL = Workplace Exposure Limits

### STYRENE (CAS: 100-42-5)

Ingredient Comments

WEL = Workplace Exposure Limits

## 8.2. Exposure controls

Protective equipment



Engineering measures

Explosion-proof general and local exhaust ventilation.

Respiratory equipment

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit.

Hand protection

Use protective gloves.

Eye protection

Wear approved safety goggles.

Other Protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Appearance	Paste
Colour	White.
Odour	Strong. Acrylic.
Flash point (°C)	11 CC (Closed cup).

### 9.2. Other information

## SECTION 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

### 10.2. Chemical stability

Stable under normal temperature conditions.

### 10.3. Possibility of hazardous reactions

### 10.4. Conditions to avoid

## CRYSTIC CRESTABOND M1-20 CARTRIDGE

Avoid heat. Avoid contact with oxidisers or reducing agents.

### **10.5. Incompatible materials**

### **10.6. Hazardous decomposition products**

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

## SECTION 11: TOXICOLOGICAL INFORMATION

### **11.1. Information on toxicological effects**

Toxicological information

No information available.

Inhalation

Harmful by inhalation. High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting. Vapour from this chemical can be hazardous when inhaled. Vapours may cause headache, fatigue, dizziness and nausea.

Ingestion

May cause stomach pain or vomiting.

Skin contact

Acts as a defatting agent on skin. May cause cracking of skin, and eczema.

Eye contact

Irritation of eyes and mucous membranes.

Medical Symptoms

Irritation of eyes and mucous membranes.

## SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

The product contains a substance which is harmful to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

### **12.1. Toxicity**

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment

### **12.2. Persistence and degradability**

No data available.

### **12.3. Bioaccumulative potential**

Bioaccumulative potential

No data available.

### **12.4. Mobility in soil**

Mobility:

No data available.

### **12.5. Results of PBT and vPvB assessment**

No data available.

### **12.6. Other adverse effects**

No data available.

## SECTION 13: DISPOSAL CONSIDERATIONS

### **13.1. Waste treatment methods**

Dispose of waste and residues in accordance with local authority requirements.

## SECTION 14: TRANSPORT INFORMATION

**CRYSTIC CRESTABOND M1-20 CARTRIDGE****14.1. UN number**

UN No. (ADR/RID/ADN)	1133
UN No. (IMDG)	1133
UN No. (ICAO)	1133

**14.2. UN proper shipping name**

Proper Shipping Name	ADHESIVES
----------------------	-----------

**14.3. Transport hazard class(es)**

ADR/RID/ADN Class	3
ADR/RID/ADN Class	Class 3: Flammable liquids.
ADR Label No.	3
IMDG Class	3
ICAO Class/Division	3
Transport Labels	

**14.4. Packing group**

ADR/RID/ADN Packing group	II
IMDG Packing group	II
ICAO Packing group	II

**14.5. Environmental hazards**

Environmentally Hazardous Substance/Marine Pollutant  
No.

**14.6. Special precautions for user**

EMS	F-E, S-D
Emergency Action Code	•3YE
Hazard No. (ADR)	33
Tunnel Restriction Code	(D/E)

**14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code****SECTION 15: REGULATORY INFORMATION****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

EU Legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

**15.2. Chemical Safety Assessment****SECTION 16: OTHER INFORMATION**

Revision Date 03/04/2013

**CRYSTIC CRESTABOND M1-20 CARTRIDGE**

Revision	12
Risk Phrases In Full	
R34	Causes burns.
R35	Causes severe burns.
R10	Flammable.
R20	Harmful by inhalation.
R21/22	Harmful in contact with skin and if swallowed.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R11	Highly flammable
R36/38	Irritating to eyes and skin.
R36	Irritating to eyes.
R37/38	Irritating to respiratory system and skin.
R37	Irritating to respiratory system.
R43	May cause sensitisation by skin contact.
R2	Risk of explosion by shock, friction, fire or other sources of ignition.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Hazard Statements In Full	
H319	Causes serious eye irritation.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H226	Flammable liquid and vapour.
H332	Harmful if inhaled.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H412	Harmful to aquatic life with long lasting effects.
H241	Heating may cause a fire or explosion.
H225	Highly flammable liquid and vapour.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
H411	Toxic to aquatic life with long lasting effects.
H410	Very toxic to aquatic life with long lasting effects.
H400	Very toxic to aquatic life.