

Revision 0



SAFETY DATA SHEET
CRYSTIC CRESTABOND M1-90 (PD10465) CARTRIDGE

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name CRYSTIC CRESTABOND M1-90 (PD10465) CARTRIDGE
 Product No. OL1174

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Adhesive.

1.3. Details of the supplier of the safety data sheet

Supplier Scott Bader
 Wollaston
 Wellingborough
 Northamptonshire. NN29 7RL
 Tel: +44(0)1933 663100
 Emergency (24 hours) +44(0)1933 663399
 Fax: +44(0)1933 663693
 E-mail: reach@scottbader.com
 Contact Person Regulatory Affairs Manager

1.4. Emergency telephone number

National Emergency Telephone Number
 +44(0)1933 663399

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (1999/45/EEC) Xi;R36/37/38. R43. F;R11. R52/53.

2.2. Label elements

Contains METHYL METHACRYLATE

Labelling



Irritant



Highly flammable

Risk Phrases

R11	Highly flammable
R36/37/38	Irritating to eyes, respiratory system and skin.
R43	May cause sensitisation by skin contact.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety Phrases

S9	Keep container in a well-ventilated place.
S16	Keep away from sources of ignition - No smoking.
S24/25	Avoid contact with skin and eyes.
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S37	Wear suitable gloves.
S51	Use only in well-ventilated areas.
S60	This material and its container must be disposed of as hazardous waste.

2.3. Other hazards

CRYSTIC CRESTABOND M1-90 (PD10465) CARTRIDGE

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

2-HYDROXYETHYL ACRYLATE		<0.2%
CAS-No.: 818-61-1	EC No.: 212-454-9	
Classification (EC 1272/2008) Acute Tox. 3 - H311 Skin Corr. 1B - H314 Skin Sens. 1 - H317 Aquatic Acute 1 - H400	Classification (67/548/EEC) T;R24 C;R34 R43 N;R50	
BENZOYL PEROXIDE		<0.4%
CAS-No.: 94-36-0	EC No.: 202-327-6	
Classification (EC 1272/2008) Org. Perox. B - H241 Eye Irrit. 2 - H319 Skin Sens. 1 - H317	Classification (67/548/EEC) E;R2 R43 Xi;R36	
DIBUTYL MALEATE		<0.2%
CAS-No.: 105-76-0	EC No.: 203-328-4	
Classification (EC 1272/2008) Skin Sens. 1 - H317 Aquatic Chronic 2 - H411	Classification (67/548/EEC) N;R51/53. R43.	
DIPROPYLENE GLYCOL DIBENZOATE		6-8%
CAS-No.: 27138-31-4	EC No.: 248-258-5	
Classification (EC 1272/2008) Aquatic Chronic 2 - H411	Classification (67/548/EEC) N;R51/53.	
METHACRYLIC ACID		2-4%
CAS-No.: 79-41-4	EC No.: 201-204-4	
Classification (EC 1272/2008) Acute Tox. 4 - H302 Acute Tox. 4 - H312 Skin Corr. 1A - H314 STOT SE 3 - H335	Classification (67/548/EEC) C;R35 Xn;R21/22	
METHYL METHACRYLATE		40-45%
CAS-No.: 80-62-6	EC No.: 201-297-1	

CRYSTIC CRESTABOND M1-90 (PD10465) CARTRIDGE

Classification (EC 1272/2008) Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 Skin Sens. 1 - H317 STOT SE 3 - H335	Classification (67/548/EEC) F;R11 R43 Xi;R37/38
---	--

STYRENE	4-6%
CAS-No.: 100-42-5	EC No.: 202-851-5

Classification (EC 1272/2008) Flam. Liq. 3 - H226 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319	Classification (67/548/EEC) Xn;R20. Xi;R36/38. R10.
--	--

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Composition Comments

Urethane Acrylate Resin in reactive solvent

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General information

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

Inhalation

Move the exposed person to fresh air at once. For breathing difficulties oxygen may be necessary. If breathing stops, provide artificial respiration. Keep the affected person warm and at rest. Get prompt medical attention.

Ingestion

DO NOT INDUCE VOMITING! NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Remove victim immediately from source of exposure. Immediately rinse mouth and provide fresh air. Get medical attention immediately! NOTE! Keep affected person away from heat, sparks and flames!

Skin contact

Remove affected person from source of contamination. Wash the skin immediately with soap and water. Get medical attention if irritation persists after washing.

Eye contact

Remove victim immediately from source of exposure. Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Contact physician if irritation persists.

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media

Fire can be extinguished using: Foam. Dry chemicals, sand, dolomite etc.

5.2. Special hazards arising from the substance or mixture

Unusual Fire & Explosion Hazards

HIGHLY FLAMMABLE! Vapours are heavier than air and may spread near ground to sources of ignition.

5.3. Advice for firefighters

Special Fire Fighting Procedures

Move container from fire area if it can be done without risk. Containers close to fire should be removed or cooled with water. Cool containers exposed to flames with water until well after the fire is out. Keep run-off water out of sewers and water sources. Dike for water control.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

CRYSTIC CRESTABOND M1-90 (PD10465) CARTRIDGE

6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Stop leak if possible without risk. Provide ventilation and confine spill. Do not allow runoff to sewer. Absorb in vermiculite, dry sand or earth and place into containers.

6.4. Reference to other sections

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Static electricity and formation of sparks must be prevented. Keep away from heat, sparks and open flame. Use explosion proof electric equipment. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

Storage Class

Flammable liquid storage.

7.3. Specific end use(s)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
METHACRYLIC ACID	WEL	20 ppm	72 mg/m ³	40 ppm	143 mg/m ³	
METHYL METHACRYLATE	WEL	50 ppm	208 mg/m ³	100 ppm	416 mg/m ³	
STYRENE	WEL	100 ppm	430 mg/m ³	250 ppm	1080 mg/m ³	

WEL = Workplace Exposure Limit.

Ingredient Comments

WEL = Workplace Exposure Limits

METHYL METHACRYLATE (CAS: 80-62-6)

Ingredient Comments

WEL = Workplace Exposure Limits

STYRENE (CAS: 100-42-5)

Ingredient Comments

WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment



Engineering measures

Explosion-proof general and local exhaust ventilation.

Respiratory equipment

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit.

Hand protection

Use protective gloves.

Eye protection

Wear approved safety goggles.

Other Protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

CRYSTIC CRESTABOND M1-90 (PD10465) CARTRIDGE

Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance	Paste
Colour	White.
Odour	Strong. Acrylic.
Flash point (°C)	8 CC (Closed cup).

9.2. Other information

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

10.2. Chemical stability

Stable under normal temperature conditions.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Avoid heat. Avoid contact with oxidisers or reducing agents.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO₂).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Toxicological information

No information available.

Inhalation

Harmful by inhalation. High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting. Vapour from this chemical can be hazardous when inhaled. Vapours may cause headache, fatigue, dizziness and nausea.

Ingestion

May cause stomach pain or vomiting.

Skin contact

Acts as a defatting agent on skin. May cause cracking of skin, and eczema.

Eye contact

Irritation of eyes and mucous membranes.

Medical Symptoms

Irritation of eyes and mucous membranes.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

The product contains a substance which is harmful to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

12.1. Toxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment

CRYSTIC CRESTABOND M1-90 (PD10465) CARTRIDGE**12.2. Persistence and degradability**

No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential

No data available.

12.4. Mobility in soil

Mobility:

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

SECTION 13: DISPOSAL CONSIDERATIONS**13.1. Waste treatment methods**

Dispose of waste and residues in accordance with local authority requirements.

SECTION 14: TRANSPORT INFORMATION**14.1. UN number**

UN No. (ADR/RID/ADN)	1133
UN No. (IMDG)	1133
UN No. (ICAO)	1133

14.2. UN proper shipping name

Proper Shipping Name ADHESIVES

14.3. Transport hazard class(es)

ADR/RID/ADN Class	3
ADR/RID/ADN Class	Class 3: Flammable liquids.
ADR Label No.	3
IMDG Class	3
ICAO Class/Division	3
Transport Labels	

**14.4. Packing group**

ADR/RID/ADN Packing group	II
IMDG Packing group	II
ICAO Packing group	II

14.5. Environmental hazardsEnvironmentally Hazardous Substance/Marine Pollutant
No.

CRYSTIC CRESTABOND M1-90 (PD10465) CARTRIDGE**14.6. Special precautions for user**

EMS	F-E, S-D
Emergency Action Code	•3YE
Hazard No. (ADR)	33
Tunnel Restriction Code	(D/E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**SECTION 15: REGULATORY INFORMATION****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

EU Legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

15.2. Chemical Safety Assessment**SECTION 16: OTHER INFORMATION**

Revision Date	02/05/2014
Revision	0
Risk Phrases In Full	
R34	Causes burns.
R35	Causes severe burns.
R10	Flammable.
R20	Harmful by inhalation.
R21/22	Harmful in contact with skin and if swallowed.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R11	Highly flammable
R36/38	Irritating to eyes and skin.
R36/37/38	Irritating to eyes, respiratory system and skin.
R36	Irritating to eyes.
R37/38	Irritating to respiratory system and skin.
R37	Irritating to respiratory system.
R43	May cause sensitisation by skin contact.
R2	Risk of explosion by shock, friction, fire or other sources of ignition.
R24	Toxic in contact with skin.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R50	Very toxic to aquatic organisms.

CRYSTIC CRESTABOND M1-90 (PD10465) CARTRIDGE

Hazard Statements In Full

H319	Causes serious eye irritation.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H226	Flammable liquid and vapour.
H332	Harmful if inhaled.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H412	Harmful to aquatic life with long lasting effects.
H241	Heating may cause a fire or explosion.
H225	Highly flammable liquid and vapour.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
H311	Toxic in contact with skin.
H411	Toxic to aquatic life with long lasting effects.
H400	Very toxic to aquatic life.